

LUXE PRO FLEX I

PRODUCT SPECIFICATIONS

Size	7" x 48"
Thickness	2 mm
Wear Layer	8 mil
Finish	ProGuard MBT
Micro Beveled Edge	No
Traffic Use	Light Commercial
Installation	Direct Glue
Recommended Adhesive	SAR 5000 (Pressure Sensitive Adhesive)
Pieces Per Carton	14
SF Per Carton	32.7
Cartons Per Pallet	85
SF Per Pallet	2,779.50
Material	100% Virgin

WARRANTY

7 Year Commercial / 10 Year Residential

PERFORMANCE

ASTM F2055 Size and Tolerance	ASTM E648 Critical Radiant Flux	Pass 0.011 in / ft < 0.020 in / ft
ASTM F386 Thickness	ASTM E662 Optical Smoke Density	Pass No change / slight change
ASTM F2055 Squareness	ASTM C1028 Slip Resistance	Pass < 8 (delta E) average
ASTM F1914 Residual Indentation	ASTM F970 Static Load	Pass < 8 (delta E) average
ASTM F137 Flexibility	Pass As specified 0.016 in / lin ft	Class 1 (< 0.45 w/cm2)
ASTM F2199 Dimensional Stability	Pass As specified 0.005 in / lin ft	Passes <450
ASTM F925 Chemical Resistance	Pass Maximum 0.010 in	Pass ADA Compliant (> 0.50)
ASTM F1514 Resistance to Heat	Pass Average < 8%	Pass 1000 psi / 250 psi (< 0.005 in)
ASTM F1515 Resistance to Light	Passes 6mm mandrel / no crack or break	