

# LUXE PRO FLEX I

## PRODUCT SPECIFICATIONS

	7" x 48"
	2 mm
	8 mil
	ProGuard MBT
DP	No
	Light Commercial
	Direct Glue
	SAR 5000 (Pressure Sensitive Adhesive)
WW	14
W	32.7
WW	85
WW	2,779.50
D	100% Virgin

## WARRANTY

7 Year Commercial / 10 Year Residential

## PERFORMANCE

ASTM F2055 Size and Tolerance	ASTM E648 Critical Radiant Flux	Pass 0.011 in / ft < 0.020 in / ft
ASTM F386 Thickness	ASTM E662 Optical Smoke Density	Pass No change / slight change
ASTM F2055 Squareness	ASTM C1028 Slip Resistance	Pass < 8 (delta E) average
ASTM F1914 Residual Indentation	ASTM F970 Static Load	Pass < 8 (delta E) average
ASTM F137 Flexibility	Pass As specified 0.016 in / lin ft	Class 1 (< 0.45 w/cm2)
ASTM F2199 Dimensional Stability	Pass As specified 0.005 in / lin ft	Passes <450
ASTM F925 Chemical Resistance	Pass Maximum 0.010 in	Pass ADA Compliant (> 0.50)
ASTM F1514 Resistance to Heat	Pass Average < 8%	Pass 1000 psi / 250 psi (< 0.005 in)
ASTM F1515 Resistance to Light	Passes 6mm mandrel / no crack or break	

