

# LUXE PRO FLEX III (T)

## PRODUCT SPECIFICATIONS

Size	11' x 17'	1	(T 2, T 3, T 4)
Thickness	2.0	mm	
Wear Layer	2.0	20 mil	
Finish	W2	ProGuard	
Square Edge	z2	Yes	
Traffic Use	F22	Heavy Commercial	
Installation	1	Direct Glue	
Recommended Adhesive	1 (Pressure Sensitive Adhesive)	SAR 5000 (Pressure Sensitive Adhesive)	
Pieces Per Carton		10	
SF Per Carton	5	5	
Cartons Per Pallet	5	5	
SF Per Pallet	1, 25	1, 25	
Material	100% Virgin	100% Virgin	

## WARRANTY

Warranty details available upon request.

## FEATURES

ASTM F2055 Size and Tolerance	ASTM E648 Critical Radiant Flux	Pass 0.011 in / ft < 0.020 in / ft
ASTM F2055 Thickness	ASTM E662 Optical Smoke Density	Pass No change / slight change
ASTM F2055 Squareness	ASTM C1028 Slip Resistance	Pass < 8 (delta E) average
ASTM F1914 Residual Indentation	ASTM F970 Static Load	Pass < 8 (delta E) average
ASTM F1177 Flexibility	Pass As specified 0.016 in / lin ft	Class 1 (< 0.45 w/cm2)
ASTM F2199 Dimensional Stability	Pass As specified 0.005 in / lin ft	Passes <450
ASTM F925 Chemical Resistance	Pass Maximum 0.010 in	Pass ADA Compliant (> 0.50)
ASTM F1514 Resistance to Stain	Pass Average < 8	Pass 1000 psi / 250 psi (< 0.005 in)
ASTM F1515 Resistance to Light	Passes 6mm mandrel / no crack or break	

